

(C)
A1

associated subscriber profile including selected information services, a method for providing information services to a subscriber, comprising:

- detecting an off-hook condition at a subscriber telephone line;
- determining the information services selected by the subscriber; and
- in response to the off-hook condition, generating a message corresponding to the selected information services for receipt by the subscriber, wherein the step of determining comprises correlating the subscriber directory number with the selected information services in the subscriber's profile.

Sub
(C3)

16. (Once Amended) In a wireless communication network comprising a plurality of subscriber telephone lines, each coupled to an associated telephone switching facility, each subscriber telephone line having at least one directory number and an associated subscriber profile including selected information services, a method for providing information services to a subscriber, comprising:

A2

- detecting at a switching facility an off-hook condition at a subscriber telephone line;
- determining the information services assigned to a subscriber; and,
- in response to the off-hook condition, generating an audio message corresponding to the assigned information services for receipt by the subscriber in place of dial tone, wherein the step of determining comprises correlating the subscriber directory number with the selected information services in the subscriber's profile.

Sub
(C5)

27. (Once Amended) In a communication network comprising a plurality of subscriber telephone lines, each coupled to an associated telephoning switching facility, each subscriber telephone line having at least one directory number and an associated subscriber profile including selected information services, a system for providing information services to a subscriber, comprising:

A3